

## TECHNICAL DATA SHEET

## **FAMILY**

TRADE NAME OF THE PRODUCT: **FAMILY** 

UNI EN 14354:2017 PRODUCT REFERENCE STANDARD:

Wood veneer floor covering with multilayer built up for internal use.

**WOOD SPECIES USED:** Surface layer: Quercus spp.

PRODUCT CONSTITUTIVE ELEMENTS: First layer: oak saw veneer (available also walnut) - Second layer: Birch

plywood - Under-layer: cork.

PRODUCT FINISH: micro-bevel on all sides of the elements with a light brushed walking surface.

Finishing with Timeless, a water-based UV-drying paint with high resistance

performance

TYPE OF LAYING: floating: following the installation manual instructions scrupulously

SIZE OF THE PRODUCT:

Overall thickness of the product: 9 mm  $\pm$  0.5 - top layer 0.6 mm.

Width: 178 mm (available on request 240 mm)

1500 mm Length:

TEST	REFERENCE	VALUE
CE MARKING	EN14342:2013	CE
FORMALDEHYDE EMISSION: CHAMBER METHOD	EN 717-1:2004	E1
PENTACHLOROPHENOL	CEN/TR 14823:2003	≤5 ppm
RESISTANCE TO FIRE	UNI EN 13501-1:2018	Cfl -s1
THERMAL CONDUCTIVITY	UNI EN 14342:2013	0,13 W/mK
DURABILITY	EN 335:2007	Class 1
DENSITY	EN 323	683 ± 50 kg/m³
LOCKING SYSTEM	/	Joint 5G















